



20 Tooth, 20 Pitch,  
14.5° Pressure Angle,  
1.000 Pitch Diameter  
Per AGMA standards.

Can Be Made From # 1663.

Material: Sintered 1020 Steel  
6.5 Min. Density.

Remove Sharp Corners By Tumbling.

Finish: Black Oxide.

REV	DESCRIPTION	DATE	UNLESS OTHERWISE SPECIFIED:	<b>20T, 14.5°PA Gear</b>			<b>Tiny-Clutch</b> <b>Helander Products, Inc.</b> Clinton, Connecticut <a href="http://www.TinyClutch.com">www.TinyClutch.com</a> P = 860-669-7953   F = 860-669-6756		
A	Redraw.	9/27/12	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL $\pm .010$ TWO PLACE DECIMAL $\pm .010$ THREE PLACE DECIMAL $\pm .005$						
			<b>PROPRIETARY AND CONFIDENTIAL</b> THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF HELANDER PRODUCTS, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF HELANDER PRODUCTS, INC. IS PROHIBITED.	<b>DRAWN BY:</b> P3	<b>SCALE:</b> 2:1	<b>DATE:</b> 9/27/2012	<b>SHEET 1 OF 1</b>		
				<b>MATERIAL:</b> See Note.					